

Appl. No. 10/030,865
Amdt. dated December 11, 2003
Reply to Office Action of August 12, 2003

Amendments to the Claims

This listing replaces all previous listing of claims:

IN THE CLAIMS:

1. (Canceled)
2. (Canceled)
3. (Canceled)
4. (Canceled)
5. (Canceled)
6. (Canceled)
7. (Canceled)
8. (Canceled)
9. (Canceled)
10. (Canceled)
11. (Canceled)

12. (Currently Amended) The method according to claim 21, wherein the size of the absolute global reference section and the local sections comprises 3 to 7 data points per dimensional direction.

13. (Previously Presented) The method according to claim 21, wherein the local sections and/or the ~~absolute~~ global reference section are deformed according to a local preferred dip and preferred dip direction.

Appl. No. 10/030,865
Amdt. dated December 11, 2003
Reply to Office Action of August 12, 2003

14. (Canceled)

15. (Previously Presented) The method according to claim 13, wherein during the selection of the ~~absolute~~ global reference section, a search is carried out for the dip and dip direction exhibiting the largest similarity among the trace portions belonging to the ~~absolute~~ global reference section, whereby afterwards in the determination of the similarity between the ~~absolute~~ global reference section and local sections, the specific relative dip between the ~~absolute~~ global reference section and the local section conforming to the largest similarity is then determined in each case.

16. (Previously Presented) The method according to claim 15, wherein in addition to the data volume with the similarity values, a data volume with the determined dip values and a further data volume with the determined values of the dip direction are formed.

17. (Previously Presented) The method according to claim 21, wherein the ~~absolute~~ global reference section is supplied by a well with ascertained lithological information.

18. (Previously Presented) The method according to claim 17, wherein the ~~absolute~~ global reference section is generated synthetically by convolving down a pre-selected 3 dimensional acoustic impedance distribution from the relevant well log with a

Appl No. 10/030,865
Amdt. dated December 11, 2003
Reply to Office Action of August 12, 2003

representative wavelet.

19. (Previously Presented) The method according to claim 17, wherein the ~~absolute~~ global reference section is formed synthetically with the help of seismic 3-D modeling techniques from a geological model determined by lithological, petrophysical and/or structural parameters.

20. (Currently Amended) The method according to claim 21, wherein several different ~~absolute~~ global reference sections, given by locations of drilled holes, are compared with the local sections each in separate similarity analyses, and thus several similarity values are calculated for each data point.

21. (Previously Presented) A method for processing a seismic 3-D measurement data set comprising a multitude of traces, each trace having a sequence of data points provided with amplitude values or acoustic impedances, which comprises the steps of:

(a) selecting an a ~~absolute~~ global reference section at a predetermined location and depth which comprises neighboring trace portions of several seismic traces;

(b) determining the similarity between the selected ~~absolute~~ global reference section and local sections of seismic data from the measurement data set and allocating a similarity value based on the

Appl No. 10/030,863
Amdt. dated December 11, 2003
Reply to Office Action of August 12, 2003

determined similarity to each data point; and

(c) creating a volume of data corresponding with the measurement data set using the similarity value which has been determined and allocated to each data point as the attribute.

22. (Previously Presented) The method according to claim 13, wherein the method comprises before the step of determining the similarity between the absolute global reference section and said local section, the step of searching for a specific dip and dip direction for the absolute global reference section and each local section which results in the largest similarity of the trace portions from the absolute global reference section and each local section, whereby the search comprises an iterative determination of the similarity of neighboring trace portions that are shifted with respect to each other according to dip and dip direction.

23. (Previously Presented) The method according to claim 21, wherein said step of determining similarity includes determining the similarity between several different absolute global reference sections which are compared with the local sections, and thus several similarity values are calculated for each data point.

Please add the following claim:

24. (New) A method for processing a seismic 3-D measurement

Appl. No. 10/030,863
Amdt. dated December 11, 2003
Reply to Office Action of August 12, 2003

data set comprising a multitude of traces, each trace having a sequence of data points provided with amplitude values or acoustic impedances, which consists of the following steps:

(a) selecting a global reference section at a predetermined location and depth which comprises neighboring trace portions of several seismic traces;

(b) determining the similarity between said selected global reference section, and each of a plurality of local sections of seismic data taken from the measurement data set;

(c) creating a new data set by assigning the calculated similarity values as attributes to the center points of each of the local sections, thus creating a volume of data or similarity attributes corresponding to the measurement data set with the determined similarity values assigned to each data point in said new data set.